



调心球轴承尺寸表 size of self-aligning bearing

轴承型号 Bearing No.	外型尺寸 (mm) Boundary dimensions (mm)				相关安装尺寸 (mm) Mounting dimensions (mm)			重量 weight			轴承型号 Bearing No.
	d	D	B	r	da	Da	ra	参考 refer (kg)			
					min	max	max	ZR02	SI3N4	POM	
135CE	5	19	6	0.3	7	17	0.3	0.0070	0.0040	0.0016	P135
126CE	6	19	6	0.3	8	17	0.3	0.0070	0.0040	0.0016	P126
127CE	7	22	7	0.3	9	20	0.3	0.0110	0.0060	0.0026	P127
108CE	8	22	7	0.3	10	20	0.3	0.0110	0.0060	0.0026	P108
129CE	9	26	8	0.6	13	22	0.6	0.0170	0.0090	0.0040	P129
1200CE	10	30	9	0.6	14	26	0.6	0.0260	0.0140	0.0061	P1200
2200CE		30	14	0.6	14	26	0.6	0.0360	0.0190	0.0084	P2200
1300CE		35	11	0.6	14	31	0.6	0.0450	0.0240	0.0105	P1300
2300CE		35	17	0.6	14	31	0.6	0.0650	0.0350	0.0152	P2300
1201CE	12	32	10	0.6	16	28	0.6	0.0310	0.0160	0.0072	P1201
2201CE		32	14	0.6	16	28	0.6	0.0410	0.0220	0.0096	P2201
1301CE		37	12	1	17	32	1	0.0520	0.0270	0.0121	P1301
2301CE		37	17	1	17	32	1	0.0730	0.0390	0.0170	P2301
1202CE	15	35	11	0.6	19	31	0.6	0.0380	0.0200	0.0089	P1202
2202CE		35	14	0.6	19	31	0.6	0.0460	0.0250	0.0107	P2202
1302CE		42	13	1	20	37	1	0.0720	0.0390	0.0168	P1302
2302CE		42	17	1	20	37	1	0.0880	0.0470	0.0205	P2302
1203CE	17	40	12	0.6	21	36	0.6	0.0560	0.0300	0.0131	P1203
2203CE		40	16	0.6	21	36	0.6	0.0680	0.0360	0.0159	P2203
1303CE		47	14	1	22	42	1	0.1000	0.0530	0.0233	P1303
2303CE		47	19	1	22	42	1	0.1200	0.0650	0.0280	P2303
1204CE	20	47	14	1	25	42	1	0.0900	0.0490	0.0210	P1204
2204CE		47	18	1	25	42	1	0.1100	0.0570	0.0257	P2204
1304CE		52	15	1.1	26.5	45.5	1	0.1300	0.0670	0.0303	P1304
1604CE		52	21	1.1	26.5	45.5	1	0.1600	0.0860	0.0373	P1304
1205CE	25	52	15	1	30	47	1	0.1100	0.0580	0.0257	P1205
2205CE		52	18	1	30	47	1	0.1300	0.0670	0.0303	P2205
1305CE		62	17	1.1	31.5	55.5	1	0.2000	0.1100	0.0467	P1305
2305CE		62	24	1.1	31.5	55.5	1	0.2600	0.1400	0.0607	P2305
1206CE	30	62	16	1	35	57	1	0.1700	0.0900	0.0397	P1206
2206CE		62	20	1	35	57	1	0.2000	0.1100	0.0467	P2206
1306CE		72	19	1.1	36.5	65.5	1	0.3000	0.1600	0.0700	P1306
2306CE		72	27	1.1	36.5	65.5	1	0.3800	0.2100	0.0887	P2306
1207CE	35	72	17	1.1	41.5	65.5	1	0.2500	0.1300	0.0583	P1207
2207CE		72	23	1.1	41.5	65.5	1	0.3100	0.1700	0.0723	P2207
1307CE		80	21	1.5	43	72	1.5	0.3900	0.2100	0.0910	P1307
2307CE		80	31	1.5	43	72	1.5	0.5200	0.2800	0.1213	P2307

轴承型号 Bearing No.	外型尺寸 (mm) Boundary dimensions (mm)				相关安装尺寸 (mm) Mounting dimensions (mm)			重量 weight			轴承型号 Bearing No.
	d	D	B	r	da	Da	ra	参考 refer (kg)			
					min	max	max	ZR02	SI3N4	POM	
1208CE	40	80	18	1.1	46.5	73.5	1	0.3200	0.1700	0.0747	P1208
2208CE		80	23	1.1	46.5	73.5	1	0.3900	0.2100	0.0910	P2208
1308CE		90	23	1.5	48	82	1.5	0.5500	0.2900	0.1283	P1308
2308CE		90	33	1.5	48	82	1.5	0.7100	0.3800	0.1657	P2308
1209CE	45	85	19	1.1	51.5	78.5	1	0.3600	0.1900	0.0840	P1209
2209CE		85	23	1.1	51.5	78.5	1	0.4200	0.2200	0.0980	P2209
1309CE		100	25	1.5	53	92	1.5	0.7400	0.3900	0.1727	P1309
2309CE		100	36	1.5	53	92	1.5	0.9500	0.5000	0.2217	P2309
1210CE	50	90	20	1.1	56.5	83.5	1	0.4000	0.2200	0.0933	P1210
2210CE		90	23	1.1	56.5	83.5	1	0.4500	0.2400	0.1050	P2210
1310CE		110	27	2	59	101	2	0.9300	0.5000	0.2170	P1310
2310CE		110	40	2	59	101	2	1.2600	0.6700	0.2940	P2310
1211CE	55	100	21	1.5	63	92	1.5	0.5400	0.2900	0.1260	P1211
2211CE		100	25	1.5	63	92	1.5	0.6200	0.3300	0.1447	P2211
1311CE		120	29	2	64	111	2	1.2200	0.6500	0.2847	P1311
2311CE		120	43	2	64	111	2	1.6200	0.8600	0.3780	P2311
1212CE	60	110	22	1.5	68	102	1.5	0.6900	0.3700	0.1610	P1212
2212CE		110	28	1.5	68	102	1.5	0.8400	0.4500	0.1960	P2212
1312CE		130	31	2.1	71	119	2	1.5100	0.8000	0.3523	P1312
2312CE		130	46	2.1	71	119	2	2.0000	1.0700	0.4667	P2312
1213CE	65	120	23	1.5	73	112	1.5	0.8800	0.4700	0.2053	P1213
2213CE		120	31	1.5	73	112	1.5	1.1200	0.6000	0.2613	P2213
1313CE		140	33	2.1	76	129	2	1.8800	1.0100	0.4387	P1313
2313CE		140	48	2.1	76	129	2	2.4800	1.3300	0.5787	P2313
1214CE	70	125	24	1.5	78	117	1.5	0.9700	0.5200	0.2263	P1214
2214CE		125	31	1.5	78	117	1.5	1.1700	0.6200	0.2730	P2214
1314CE		150	35	2.1	81	139	2	2.3000	1.2300	0.5367	P1314
2314CE		150	51	2.1	81	139	2	3.2500	1.7400	0.7583	P2314
1215CE	75	130	25	1.5	83	122	1.5	1.0500	0.5600	0.2450	P1215
2215CE		130	31	1.5	83	122	1.5	1.2500	0.6600	0.2917	P2215
1315CE		160	37	2.1	86	149	2	2.7684	1.6164	0.7112	P1315
2315CE		160	55	2.1	86	149	2	3.6140	2.1103	0.9070	P2315
1216CE	80	140	26	2	89	131	2	1.2800	0.6900	0.2987	P1216
2216CE		140	33	2	89	131	2	1.5500	0.8200	0.3617	P2216
1316CE		170	39	2.2	91	159	2.2	3.2300	1.8850	0.8100	P1316
2316CE		170	58	2.2	91	159	2.2	4.3800	2.5590	1.0960	P2316
1217CE	85	150	28	2	94	141	2	1.5900	0.8500	0.3710	P1217
2217CE		150	36	2	94	141	2	1.9400	1.0300	0.4527	P2217
1317CE		180	41	2.2	96	169	2.2	3.8450	2.2450	0.9650	P1317
2317CE		180	60	2.2	96	169	2.2	5.1500	3.0000	1.2900	P2317
1218CE	90	160	30	2	100	150	2	1.9230	1.1225	0.4830	P1218
2218CE		160	40	2	100	150	2	2.4760	1.4450	0.6280	P2218
1318CE		190	43	2.5	105	179	2.5	4.6140	2.2690	0.9870	P1318
2318CE		190	64	2.5	105	179	2.5	6.0750	3.5470	1.5500	P2318
1219CE	95	170	32	2.2	106	160	2.2	2.3070	1.3470	0.5800	P1219
2219CE		170	43	2.2	106	160	2.2	3.2298	1.8858	0.8200	P2219
1319CE		200	45	2.5	110	189	2.5	5.3830	3.1430	1.3500	P1319
2319CE		200	67	2.5	110	189	2.5	7.0750	4.1308	1.8600	P2319